

APPLICATIONS

- ANALOG & DIGITAL VIDEO
- STUDIO TIE LINES
- PATCH CORDS
- RACK WIRING
- SATELLITE HEADENDS
- OB VANS

FEATURES

- Canare 75Ω BNC, F or RCA Crimp Plugs
- Super Flexible, easy payout & wrap-up
- High Density Copper Braid, or Foil + Braid Shields
- Variety of Matte Finish Jacket Colors
- 100% Test and Quality Controlled
- Excellent Connector Pull Strength
- Color Matching Strain Relief Boots

VAC • 75Ω BNC (RG59) VIDEO CORDS

Our high quality **RG59B/U** 75Ω BNC-BNC cord is perfect for patching, rack wiring or layout between video plant equipment. All models are super flexible and come pre-assembled with 2 color matched cable strain relief boots. Canare cable and connectors offer excellent performance because they are 75Ω impedance matched for cleaner and sharper video resolution.



VIC • 75Ω BNC (8281F) VIDEO CORDS

Canare VIC cords are useful for both inter-rack harness wiring and longer video cable runs. This super flexible **8281F** type pre-made 75Ω BNC-BNC assembly is available in a variety of colors. Our low loss cord offers outstanding video bandwidth performance because all components used are impedance matched for cleaner and sharper video resolution.



STANDARD STOCK • 75Ω VIDEO CORDS				
MODEL	Lng.	75Ω Coax Cable	75Ω BNC Crimp Plugs	Color Boot
VAC003F	3ft	LV-61S	BCP-C4B	CB04
VAC006F	6ft			
VAC010F	10ft			
VAC025F	25ft			

COLORS AVAILABLE									
BLK	BLU	BRN	GRY	GRN	ORN	PPL	RED	WHT	YEL
VAC	■	■	■	■	■	■	■	□	■

STANDARD STOCK • 75Ω VIDEO CORDS				
MODEL	Lng.	75Ω Coax Cable	75Ω BNC Crimp Plugs	Color Boot
VIC010F	10ft	LV-77S	BCP-C77A	No
VIC025F	25ft			
VIC050F	50ft			
VIC100F	100ft			

COLORS AVAILABLE									
BLK	BLU	BRN	GRY	GRN	ORN	PPL	RED	WHT	YEL
VIC	■	■	■	■	■	■	■	○	■

□ = Standard Stock ○ = Special Order

75Ω F CORDS

Premium RF video line cords can now be special ordered using our new **FP-C** series 2GHz crimp connector. Choose from a wide assortment of jacket colors and lengths of Canare standard analog or low loss digital 75Ω Video Coax Cables.



75Ω RCA VIDEO CORDS

RCA video patch cords can now be special ordered. Made with our new **RCAP** series 200MHz crimp connector. Choose from a wide assortment of Canare 75Ω Video Coax Cables. Perfect for SPDIF Digital Audio and MultiMedia.



Custom Model Selection Guide

B02B005F BLACK

- 1st End Connector Type**
 B = 75Ω BNC Crimp Plug (BCP-C)
 F = 75Ω F Crimp Plug (FP-C)
 R = 75Ω type RCA Crimp Plug (RCAP-C)
- 75Ω COAX Cable Type**
 01 = L-1.5C2VS
 02 = L-3C2VS
 03 = LV-61S
 04 = LV-77S
 05 = L-2.5CFB
 06 = L-3CFB
 07 = L-4CFB
 08 = L-5CFB
 09 = L-7CFB
- Cable Color**
 BLACK, BLUE, BROWN, GRAY, GREEN
 ORANGE, PURPLE, RED, WHITE, YELLOW
- Boot**
 BLANK = 2ea Matching Color CB Boots
 X = No Boots
 S = Other CB Boot Colors
- Length (feet)**
 1, 2, 3, 5, 8, 10, 15, 30, 50, 100
Other Custom Lengths are available
- 2nd End Connector Type**
 B = 75Ω BNC Crimp Plug
 F = 75Ω F Crimp Plug
 R = 75Ω type RCA Crimp Plug
 X = Blunt Cut

		NOMINAL ATTENUATION VALUE								
		1 MHz	10 MHz	50 MHz	100 MHz	200 MHz	400 MHz	700 MHz	900 MHz	1 GHz
L-3C2VS	dB/100 ft	0.5	1.5	3.2	4.7	6.7	9.4	12.5	14.2	14.9
	dB/100m	1.5	4.9	10.4	15.5	21.9	31.0	41.0	46.5	49.0
LV-61S	dB/100 ft	0.4	1.3	2.7	4.1	5.7	8.1	10.7	12.1	12.8
	dB/100m	1.3	4.2	9.0	13.3	18.8	26.6	35.1	39.8	42.0
LV-77S	dB/100 ft	0.3	1.0	2.4	3.3	4.6	6.6	8.6	9.8	10.4
	dB/100m	1.1	3.4	7.8	10.8	15.2	21.5	28.4	32.3	34.0
L-3CFB	dB/100 ft	0.3	1.0	2.5	3.3	4.5	6.5	8.8	10.1	10.6
	dB/100m	1.1	3.2	8.0	10.7	14.7	21.3	28.9	33.0	34.8
L-4CFB	dB/100 ft	0.3	0.9	2.0	2.7	3.8	5.4	7.3	8.4	8.9
	dB/100m	1.0	2.9	6.7	8.9	12.4	17.7	24.0	27.6	29.3
L-5CFB	dB/100 ft	0.3	0.5	1.6	2.2	3.0	4.3	6.0	6.8	7.2
	dB/100m	0.8	1.6	5.3	7.1	9.9	14.2	19.5	22.2	23.7
L-7CFB	dB/100 ft	0.2	0.5	1.2	1.6	2.1	3.1	4.2	4.8	5.1
	dB/100m	0.7	1.6	3.9	5.2	6.9	10.0	13.8	15.7	16.7