

OG-DA-HDTV-SDI HDMI TO SDI CONVERTER

Key Features

- openGear 3.0 card-based form factor
- 1 x HDMI input
- 1 x RJ45 HDMI receiver input for Apantac CATx extenders
- 1 x HDMI loop out
- 2 x SDI outputs (3G/HD/SD-SDI)
- Cable reach up to 120 m for 3G, 140 m for HD-SD-SDI
- Built-in simple multi-format color bar generator
- Low power consumption - 15W
- Built-in interlacer - change 1080P to 1080i
- 5 year limited warranty

How to Order

- OG-DA-HDTV-SDI-SET-1: OG-DA-HDTV-SDI-MB + OG-DA-HDTV-SDI-RM

Rear Module Options (Occupies 2 Slots)

OG-DA-HDTV-SDI-RM

- 1 x HDMI Input
- 1 x RJ45 Input (Extended HDMI input)
- 1 x HDMI loop out
- 2 x BNC outputs (Reclocked SDI out)

OG-DA-HDTV-SDI-RM2 (Dual RM)

SIDE-A

- 1 x HDMI input
- 2 x BNC outputs (Reclocked SDI out)

SIDE-B

- 1 x HDMI input
- 2 x BNC outputs (Reclocked SDI out)

SPECIFICATIONS

Inputs	HDMI, Extended HDMI with RJ45 (RM only, not RM2)	Output	2 x Reclocked SDI
Analog Audio Output	35 mm phone jack (RM only, not RM2)	Loop out	1 x HDMI (RM only, not RM 2)

