

ACTIONHL-700HD

FEATURE

1. 16:9 HIGH LIGHT LCD PANEL, RESOLUTION 1024*600
2. BRIGHTNESS WAVEFORM DISPLAY
3. FALSE COLOR
- 4.SAFETY MARKS/TALLY
5. B&W, BLUE ONLY
6. SDI 1/1.001
7. HDMI 1.4
8. 16 CHANNEL AUDIO METERS(DISPLAY 8 CHANNELS. SELECTABLE)
9. SAFE MARKER, FRAME, SUBTITLE FRAME
10. 4:3、16:9、LETTER BOX、OVERSCAN
11. KEY LOCK FEATURE
12. BUILT IN 3D-LUT(REC709、SMPTE、EBU)
13. SELF DEFINED 3D-LUT H/V-DELAY
- 14.BATTERY CHECKING
15. HDMI TO SDI OUTPUT
16. SDI TO HDMI OUTPUT
17. SDI VIDEO WAVEFORM HISTOGRAM
18. IMAGE FLIP
19. ANAMORPHIC LENSES 1.3x 2.0x
20. STILL FRAME

Specification

PANEL	SIZE	7"
	RESOLUTION	1024×RGB×600
	DOT PITCH	0.15 (H) ×0.15 (V) mm
	ASPECT RATIO	16:9 / 4:3 SWITCHABLE
	BACK LIGHT	White LED
	BRIGHTNESS (MAX)	1000cd/m ²
	CONTRAST (MAX)	700:1
	Color depth	8Bits (16.7M)
	IMAGE PROCESSING	10Bits
	RESPONSE TIME	10ms
	VIEWING ANGLE	H170° / V170°

VIDEO IN	3G/HD/SD-SDI	1 x BNC
	HDMI	1 x HDMI Type-A

VIDEO OUT	3G/HD/SD-SDI	1 x BNC
	HDMI	1 x HDMI Type-A

AUDIO	SDI audio demultiplexing	yes
	audio meters	16 channels
	headphone	yes

Operation requirement	Input voltage	12V DC four pin XLR
	Power consumption	25W
	Working temperature	0-40°C
	Store temperature	-20-70°C
	Store humidity	0%-90% No condensation

Structure	Shell material	Aluminum profile
	Dimension (mm)	195 x 116.2 x 24
	Weight	About 1.0KG

HDMI INPUT FORMAT

HDMI	480p/60、480i/60、576i/50、576p/50、720p(50/60)、1080i(/50/60)、1080p(24/25/30/50/60)、4096*2160p/24、3840*2160p 24/25/30
------	---

HDMI OUTPUT FORMAT

HDMI	480p/60、480i/60、576i/50、576p/50、720p(50/60)、1080i(/50/60)、1080p(24/25/30/50/60)
------	---

SDI INPUT/OUTPUT FORMAT

425M(3G-SDI)	1080p(50/60)
274M(HD)	1080i(60/59.94/50) 1080p(30/29.97/25/24/24sF/23.98/23.98sF)
296M(HD)	720p(60/59.94/50/30/29/25/24/23.98)
259M(SD)	480/59.94i、576/50i