

MODEL	TAHOMA-LE- SDI / COMPOSITE MULTIVIEWER with Built-in CATX Extender		
Video Inputs	4 -32 auto-detect SDI / Composite	Outputs	1-8 DVI, HDMI, VGA (option), 1 SDI (option)
Connectors	BNC IEC 61169-8 Annex A	Output Resolution	800 x 480 - 2048 x 1080 (1080p)
Total Windows	4, 8, 12, 16, 20, 24, 28, 32	Built-in CATx Extender	Up to 35 feet Extend up to 115 feet (with optional active receiver)
Serial Digital	SDI (SMPTE-259M-C)	On Screen Display	Skin Technology for customizing borders, labels (4 / window), fonts, tally LEDs, clock faces, logos, UMD, OMD, IMD, dynamic UMD
Equalization	400m at 270 Mbps with Belden 1694A	General Purpose IO	Up to 72 inputs with DB9 connectors
Return Loss	>15db up to 270Mb/s	Serial Port	RS232 with RS422 or RS485 option Connector: RJ45 Baud Rate Up to 115200 Supported Protocols: TSL, TSI, AXP
AES Audio	4 channels / video input (2 pairs, balanced / unbalanced)	IP	100 Base-TX, Supported Protocols: TSL, AXP, Connector: RJ45
Analog Stereo Audio	4 channels / video input (balanced / unbalanced)	Electrical	25W, 90-250V 50/60 Hz 100W, 90-250V 50/60 Hz 200W, 90-250V 50/60 Hz
Embedded Audio	SMPTE-272M-A	EMI/RFI	Complies with FCC Part 15, Class A, CE, EU EMC, C-tick
Alarms	No audio, audio high / low, no video, video black, video frozen, WSS, AFD	Power	Optional redundant power supply
Control	Front panel buttons for quick preset recalls, GPIs, Apantac ASCII Protocol (AXP), Director (configuration and control application)	Size	1/2 width of 1RU 21.5cm (8.5") W x 37cm (14.6") D 1RU, 44.5cm (17.5") W x 50cm (19.7") D 2RU, 44.5cm (17.5") W x 60cm (23.6") D