

System	RH45D(Head) + RT40RB(Tripod) + SP-2B(Floor spreader) + RC-50(Carrying case)		
Payload	12 kg / 26.5 lb	Tilt angle	+90° / -70° (Limited to ±40° with maximum counterbalance)
Weight	6.7 kg / 14.7 lb	Pan angle	360°
Height	① H: 1730 mm W: 710 mm (※Reference)	Counterbalance	Range : 4.5kg-10.5kg / 10-23.1lb (CG100mm)
	② H: 630 mm W: 1110 mm ( " )		System : Continuous
Folded length	③ L: 895 mm ( " )	Drag mode	Free plus 3STEP
Camera plate (Sliding range)	Sliding plate ±40 mm / ±1.6"	Ball diameter	∅75 mm
Plate attachment (Screw sliding range)	Type: 1/4-20UNC screw with video pin	Section	2STAGE (Material: Aluminum)
	76 mm / 3"	Tripod fixation	Fixing lock knob
Spare screw	Type: 1/4-20UNC, 3/8-16UNC screws	Spreader	SP-2B (Telescopic, Removable)
	Equipped on the top of the head (beneath sliding plate)	Pan handle	PH-6B
		Case material	Nylon, TPE, PE, PP, POM, ABS

### Remarks

※Counterbalance support knob is included in RS-450D

### ■Exterior Dimensions (mm)

