

| | | | |
|--|--|-----------------|---|
| System | RHP75 (Head) + RT50C (Tripod) + SP-2B (Floor spreader) + RC-70 (Carrying case) | | |
| Payload | 17 kg / 37.5 lb | Tilt angle | +90° / -70° (Limited to ±40° with maximum counterbalance) |
| Weight | 7.5 kg / 16.5 lb | Pan angle | 360° |
| Height | ① H : 1755 mm W : 710 mm (※Reference) | Counterbalance | Range : 5.5~14 kg / 12~31 lb (CG125mm) |
| | ② H : 650 mm W : 1100 mm (") | | System : Continuous |
| Folded length | ③ L : 915 mm (") | Drag mode | 7 STEP |
| Camera plate (Sliding range) | Sliding plate ±55 mm / 2.2" | Ball diameter | ∅100 mm |
| Plate attachment (Screw sliding range) | Type : 3/8-16UNC × 2 102 mm / ±4" | Section | 2STAGE (Material: Carbon) |
| Spare screw | Type : 3/8-16UNC × 1 | Tripod fixation | Fixing lock knob |
| | Equipped on the head (Behind the platform of sliding plate) | Spreader | SP-2B (Telescopic, Removable) |
| | | Pan handle | PH-8B |
| | | Case material | Nylon , Polyester , TPE , PE , PP |

Remarks

■ Exterior Dimensions (mm)

■ RHP75

