

TL-701HD / NP*

规格参数

屏幕尺寸	7"
像素	1280 (H) × 800 (V)
点距	0.117 (H) × 0.117 (V) mm
显示比例	16:9 / 4:3 可转换
亮度	400cd/m ²
对比度	800:1
响应时间	12 ms
可视角度	左右 178° / 上下 178°
电源电压	输入: AC100~240V 50/60Hz 输出: DC12V
功率消耗	≤11W
外观尺寸	L 207×H 147×D 38.5 mm
整机重量	约 1 kg

输入格式及功能

型号		TL-701HD	TL-701NP	备注
功能	复合视频	●	●	BNC×1路
	分量 (Y/Pr/Pb)	●	●	BNC×1路
	3G/HD/SD-SDI	●		BNC×1路
	HDMI	●	●	HDMI×1路
音频输入		●	●	RCA×1路 (双声道)
音频监听		●	●	前扬声器 0.5W (8Ω) 耳机: 3.5mm 标准接口
SDI 嵌入音频		●		PPM / UV
视频输出	复合视频	●	●	BNC×1路
	分量 (Y/Pr/Pb)	●	●	BNC×1路
	3G/HD/SD-SDI	●		BNC×1路
TALLY 显示		●	●	红 / 绿双色

配置清单

	TL-701HD	TL-701NP
交流电源适配器	1台	1台
遮光罩	1个	1个
双向连接器 (小云台)	1个	1个
安东电源线	1条	1条

Specification

Screen Size	7"
Resolution	1280 (H) × 800 (V)
Dot Pitch	0.117 (H) × 0.117 (V) mm
Aspect Ratio	16:9 / 4:3 Switchable
Brightness	400cd/m ²
Contrast	800:1
Response Time	12 ms
Viewing Angle	H 178° / V 178°
Voltage Input	DC12V
Power Consumption	≤11W
Monitor Size	L 207×H 147×D 38.5 mm
Weight	1 kg

Inputs & Functions

Model		TL-701HD	TL-701SD	TL-701NP	Remark
Function					
Video input	Composite	●	●	●	BNC×1 line 1.0 V _{p-p} ±3 dB
	Component (Y/Pb/Pr)	●	●	●	BNC×1 line
	SD-SDI	●	●		BNC×1 line
	HD-SDI	●			BNC×1 line
	HDMI	●	●	●	HDMI×1 line
Audio input		●	●	●	RCA×1 line (dual channel)
Audio Monitoring		●	●	●	Front Speaker 0.5W (8Ω) Earphone:3.5mm jack
SDI Embedded Audio		●	●		PPM / UV
Video output	Composite	●	●	●	BNC×1 line Loop through 75Ω automatic termination
	Component (Y/Pb/Pr)	●	●	●	BNC×1 line
	SD-SDI	●	●		BNC×1 line
	HD-SDI	●			BNC×1 line
TALLY		●	●	●	Red/green two colors

Standard Accessories

	TL-701HD	TL-701SD	TL-701NP
Switching adapter	1	1	1
Foldable Sunhood	1	1	1
Hot shoe connector	1	1	1
D-tap power cable	1	1	1

