

TL-701HDA\*

Specification

Screen Size	7"
Resolution	1280 (H) x800 (V)
Dot Pitch	0.117 (H) x0.117 (V) mm
Aspect Ratio	16:9 / 4:3 Switchable
Brightness	400cd/m <sup>2</sup>
Contrast	800:1
Response Time	12 ms
Viewing Angle	H 178° / V 178°
Voltage Input	DC12V
Power Consumption	≤12W
Operation Way	Button+Code
Monitor Size	L 207xH 147xD 38.5 mm
Weight	≤1 kg

Inputs & Functions

Function		Model	TL-701HDA	Remark
Video input	Composite		•	BNCx1 line 1.0 Vp-p±3 dB
	Component (Y/Pb/Pr)		•	BNCx1 line
	3G/HD/SD-SDI		•	BNCx2 line Brightness waveform waveform Vectorscope HV-DELAY RGB
	HDMI		•	HDMIx1 line
Audio input			•	RCAx1 line (Stereo)
Audio Monitoring			•	Front Right Speaker 0.5W ( 8Ω ) Earphone:3.5mm jack
SDI Embedded Audio			•	PPM / UV
Video output	Composite		•	BNCx1 line Loop through 75Ω automatic termination
	3G/HD/SD-SDI		•	BNCx1 line
TALLY			•	Red/green two colors

Standard Accessories

	TL-701HDA
AC-DC adapter	1
AC power cable	1
U bracket	1
HDMI plug lock	1
Foldable Sunhood	1

D-tap power cable	1
-------------------	---

---

\* As per Manufacturer Catalogue Dated: 28/08/2017