

TL-D2410HD*

FEATURE

1. 16:9 FULL HD panel 1920*1200 resolution
2. THREE WAVEFORM DISPLAY, (BRIGHTNESS/VECTSCOPE/RGB)
3. SDI, DVI SIGNAL WAVEFORM MONITORING
4. FOCUS ASSISTANT(REDF/GREEN/BLUE/YELLOW)
5. FALSE COLOR
6. ELP
7. TIME CODE
8. SAFETY MARKS/TALLY/UMD
9. DYNAMIC UMD, SUPPORT TSL3.1\TSL4.0
10. B&W, BLUE ONLY
11. SDI 1/1.001
12. HDCP 1.1
13. H/V-DELAY
14. 16 CHANNEL AUDIO METERS(DISPLAY 8 CHANNELS. SELECTABLE)
15. KEY LOCK FEATURE
16. BATTERY CHECKING
17. EMBEDDED 3D-LUT (Rec709、 SMPTE-C DCI-P3 AND EBU)
18. EMBEDDED S-LOG1、 S-LOG2、 S-LOG3、 C-LOG
19. USER-DEFINED F KEY
20. STILL FRAME

SPECIFICATION

PANEL	SIZE	24.1"
	RESOLUTION	1920×RGB×1200
	DOT PITCH	0.27 (H) ×0.27 (V) mm
	ASPECT RATIO	16:9 / 4:3
	BACK LIGHT	WLED
	BRIGHTNESS (MAX)	400cd/m ²
	CONTRAST (MAX)	1500:1
	Color depth	10Bits(1.073G colors)
	IMAGE PROCESSING	10Bits
	RESPONSE TIME	8ms
	VIEWING ANGLE	H178° / V178°

VIDEO IN	3G/HD/SD-SDI	2 x BNC
	COMPOSITE(CVBS)	1 x BNC
	DVI	1 x DVI-I

VIDEO	3G/HD/SD-SDI	1 x BNC
--------------	--------------	---------

OUT	COMPOSITE	1 x BNC
------------	-----------	---------

AUDIO	audio demultiplexing	yes
	audio meters	16 channels
	analogue audio input	2 RCA
	Speakers	2x8Ω/2W
	headphone	yes

Operation requirement	Input voltage	DC 24V
	Power consumption	45W
	Working temperature	0-40°C
	Store temperature	-20-60°C
	Store humidity	0%-90% no condensation

Structure	Shell material	Aluminum profile
	Dimension (mm)	L564.9 x H430.7 x D48mm
	Weight	Around 7.3Kg
	Installing	desktop or VESA
	VESA HOLE	100x100mm

CVBS INPUT FORMAT

CVBS	NTSC、PAL
------	----------

DVI INPUT FORMAT

DVI-D	480p/60、480i/60、576i/50、576p/50、720p(50/60)、1080i (/50/60)、1080p(24/25/30/50/60)
-------	--

SDI INPUT FORMAT

425M(3G-SD I)	1080p(50/60)
274M(HD)	1080i(60/59.94/50) 1080p(30/29.97/25/24/24sF/23.98/23.98sF)
296M(HD)	720p(60/59.94/50/30/29/25/24/23.98)
259M(SD)	480/59.94i、576/50i

Standard Accessories

	TL-D2410HD
AC-DC adapter	1
AC power cable	1
SDI cable	1
DVI to HDMI adapte	1
Desk stand	2