

# TL-P2150HD\*

## FEATURE

- 1.16:9 FULL HD 1920\*1080 ,HIGH CONTRAST PANEL
2. SDI VIDEO SIGNAL BRIGHTNESS WAVEFORM DISPLAY
- 3.FALSE COLOR
- 4.SAFETY MARKS/TALLY/UMD
- 5.B&W, BLUE ONLY
- 6.SDI 1/1.001
- 7.HDCP 1.1
- 8.H/V-DELAY
- 9.16 CHANNEL AUDIO METERS
10. SAFETY BOX, BOX, BOX LABELED SUBTITLES
11. 4: 3、 16: 9、 LETTER BOX、 OVERSCAN
- 12.LOCK FEATURE
- 13.BATTERY CHECKING
- 14.EMBEDDED 3D-LUT (Rec709、 SMPTE-C AND EBU)
- 15.F KEY USER-DEFINED
- 16.FREEZE FRAME

## SPECIFICATION

<b>PANEL</b>	SIZE	21.5"
	RESOLUTION	1920×RGB×1080
	DOT PITCH	0.2475 (H) ×0.2475 (V) mm
	ASPECT RATIO	16:9 / 4:3
	BACK LIGHT	WLED
	BRIGHTNESS (MAX)	250cd/m <sup>2</sup>
	CONTRAST (MAX)	1000:1
	Color depth	8Bits(16.7M colors)
	IMAGE PROCESSING	10Bits
	RESPONSE TIME	8ms
	VIEWING ANGLE	H178° / V178°

<b>VIDEO IN</b>	3G/HD/SD-SDI	2 x BNC
	COMPOSITE(CVBS)	1 x BNC
	DVI	1 x DVI-I

<b>VIDEO OUT</b>	3G/HD/SD-SDI	1 x BNC
	COMPOSITE	1 x BNC

<b>AUDIO</b>	audio demultiplexing	Yes
	audio meters	16 channels

	Analogue audio	Left right 2 RCA
	Speakers	2x8Ω/2W
	headset	yes

<b>Operation requirement</b>	Input voltage	DC 12V
	Power consumption	35W
	Working temperature	0-40°C
	Store temperature	-20-60°C
	Store humidity	0%-90% no condensation

<b>Structure</b>	Shell material	Aluminum profile
	Dimension (mm)	512.1x372x150
	Weight	Around 7Kg
	Fixing method	Desktop orVESA
	VESA size	100*100mm

### CVBS INPUT FORMAT

CVBS	NTSC、PAL
------	----------

### DVI-I input formats

DVI-A	VGA(640*480)、SVGA (800*600)、XGA (1024*768)、WXGA (1280*768/1280*800)、SXGA (1280*1024)、SXGA+ (1440*1050)、WSXGA (1680*1050)、UXGA (1600*1200)、WUXGA (1920*1200)
DVI-D	480p/60、480i/60、576i/50、576p/50、720p(50/60)、1080i(/50/60)、1080p(24/25/30/50/60)

### SDI input formats

425M(3G-SDI)	1080p(50/60)
274M(HD)	1080i(60/59.94/50) 1080p(30/29.97/25/24/24sF/23.98/23.98sF)
296M(HD)	720p(60/59.94/50/30/29/25/24/23.98)
259M(SD)	480/59.94i、576/50i

### Standard Accessories

	TL-P2150HD
AC-DC adapter	1
AC power cable	1
SDI cable	1
DVI to HDMI adapte	1
New Design Carry On Case	1