

TL1730HDA-CO LCD*

FEATURE

- 1.16:9 FULL HD 1920*1080 ,HIGH CONTRAST PANEL
- 2.THREE WAVEFORM DISPLAY, (BRIGHTNESS/VECTSCOPE/RGB)
3. SDI, DVI SIGNAL WAVEFORM MONITORING
- 4.FOCUS ASSISTANT(REDF/GREEN/BLUE/YELLOW)
- 5.FALSE COLOR
- 6.TIME CODE (VITC/VTC)
- 7.SAFETY MARKS/TALLY/UMD
- 8.B&W, BLUE ONLY
- 9.SDI 1/1.001
- 10.HDCP 1.1
- 11.H/V-DELAY
- 12.16 CHANNEL AUDIO METERS
- 13.LOCK FEATURE
- 14.BATTERY CHECKING
- 15.EMBEDDED 3D-LUT (Rec709、 SMPTE-C AND EBU)
- 16.F KEY USER-DEFINED
- 17.FREEZE FRAME
- 18.LOG MODE CONVERSION FUNCTION

SPECIFICATION

PANEL	SIZE	17.3"
	RESOLUTION	1920×RGB×1080
	DOT PITCH	0.199 (H) ×0.199 (V) mm
	ASPECT RATIO	16:9 / 4:3 Switchable
	BACK LIGHT	RGB LED
	BRIGHTNESS (MAX)	300cd/m ²
	CONTRAST (MAX)	800:1
	Color depth	10Bit
	IMAGE PROCESSING	10Bit
	RESPONSE TIME	10ms
	VIEWING ANGLE	H178° / V178°

VIDEO IN	3G/HD/SD-SDI	2 x BNC
	COMPOSITE(CVBS)	1 x BNC
	HDMI	1 x HDMI-A
	VGA	1 x DSUB15

VIDEO	3G/HD/SD-SDI	1 x BNC
--------------	--------------	---------

OUT	COMPOSITE	1 x BNC
------------	-----------	---------

AUDIO	audio demultiplexing	Yes
	audio meters	16 channels
	Speakers	2x8Ω/2W
	headset	yes

Operation requirement	Input voltage	DC 12V
	Power consumption	30W
	Working temperature	0-40°C
	Store temperature	-20-60°C
	Store humidity	0%-90% no condensation

Structure	Dimension (mm)	474X415X149mm
	Weight	Around 9Kg

* As per Manufacturer Catalogue Dated: 28/08/2017