

TLP890HD-2

FEATURE

1. 1920x1200 Native Resolution (IPS Technology)
2. Luminance waveform in SDI mode.
3. Grade & Step false color
4. Safety marker / Subtitle marker / TALLY / Static UMD
5. Black & white, blue, mono color switch
6. Compatible with SDI1/1.001 fps
7. HDCP 1.1 / HDMI 1.3
8. H/V Delay
9. Audio meter in 16 channels (Simultaneous display 8 channels)
10. 4:3 / 16:9 / Letter Box / Over Scan
11. Safety lock
12. Built-in 3D-LUT (REC709, SMPTE-C, EBU)
13. Fast keys (custom setting)
14. On display battery meter
15. Static-frame

SPECIFICATION

PANEL	SIZE	8.9"
	RESOLUTION	1920×RGB×1200
	DOT PITCH	0.09975 (H) ×0.09975 (V) mm
	ASPECT RATIO	16:9 / 4:3
	BACK LIGHT	WLED
	BRIGHTNESS (MAX)	500cd/m ²
	CONTRAST (MAX)	800:1
	Color depth	8Bits(16.7M colors)
	IMAGE PROCESSING	10Bits
	RESPONSE TIME	10ms
	VIEWING ANGLE	H170° / V170°

VIDEO IN	3G/HD/SD-SDI	2 x 2BNC
	COMPOSITE(CVBS)	2 x BNC
	COMPONENT	2x 3 BNC
	HDMI	2 x HDMI Type-A

VIDEO OUT	3G/HD/SD-SDI	2 x BNC
	COMPOSITE	2 x BNC

AUDIO	audio demultiplexing	Yes
--------------	----------------------	-----

	audio meters	16 channels
	Speakers	Stereo 2x8Ω/1W
	headset	yes

Operation requirement	Input voltage	DC 12V
	Power consumption	30W
	Working temperature	0-40°C
	Store temperature	-20-70°C
	Store humidity	0%-90% no condensation

Structure	Shell material	Aluminum profile
	Dimension (mm)	L482.6 x H177 x D58.5mm
	Weight	Around 3.4Kg

Standard Accessories

	TLP890HD-2
AC-DC adapter	1
AC power cable	1
Fix nut	4
SDI cable	2