

TLS480HD-4*

PANEL

Size	4.8 inch
RESOLUTION	800 (H) ×480 (V)
DOT PITCH	0.130 (H) ×0.130 (V) mm
ASPECT RATIO	16:9 / 4:3 switchable
BRIGHTNESS (MAX)	500cd/m ²
CONTRAST (MAX)	800:1
RESPONSE TIME	10ms
VIEWING ANGLE	H160° / V 160°

VIDEO IN

CVBS	BNC×1×4
3G-SDI	BNC×1×4
DVI	DVI-D×1×4

VIDEO OUT

CVBS	BNC×1×4
3G SDI	BNC×1×4

AUDIO

Analogue Audio Input	RCA 1 line×4 (dual channel)
Audio demultiplexing	Support
Audio meters	16 channels (Maximum 8 channels can be displayed at one time)
Headset	Support

VIDEO FORMAT

C
V
B
S NTSC、PAL
480p/60、480i/60、576i/50、576p/50、720p(50/60)、1080i(/50/60)、1080p(24/25/30/50/60)、VGA(640*480)、SVGA (800*600) 、XGA (1024*768) 、WXGA (1280*768/1280*800) 、SXGA (1280*1024) 、SXGA+ (1440*1050) 、WSXGA (1680*1050) 、UXGA (1600*1200) 、WUXGA (1920*1200)
3
G
-
S
D 1080p50/60

I	
H	
D	
-	
S	
D	
I	1080i/60/59.94/50、1080p/30/29.97/25/24/24sF/23.98/23.98sF、720p/60/59.94/50
S	
D	
-	
S	
D	
I	480/59.94i、576/50i

OPERATION

Input voltage	12V DC 4 pin XLR
Power consumption (MAX)	≤30W
Working temperature	0-40°C
Store temperature	-20-60°C
Store humidity	0%-90% No Condensation

STRUCTURE

Shell material	Aluminium-magnesium Alloy
Dimension (mm)	L 448×H 88.1×D 73.5 mm
Weight	1.75kg
Installing way	Rackmount

