

VF-701HDA*

FEATURE

- 1.High Contrast LCD Panel (800: 1)
- 2.High Resolution LCD Panel (1280×800)
- 3.Wide View Angle (H178°/V178°)
- 4.High Brightness、adjustable rear-mounted TALLY Light
- 5.External TALLY signal input terminal post
- 6.Assisting Focus Function
- 7.Linear zoom trigger (patent technology)
- 8.Out of range signal detect function
- 9.Monochrom (BLUE ONLY)
- 10.Safety mark, Center mark, Title frame
- 11.4: 3/16: 9、Letter box、Overscan、full screen
- 12.Safety Lock Function
- 13.F key Self-defining function F
- 14.Super-long sunhood

SPECIFICATION

PANEL	Screen Size	7"
	Resolution	1280 (H) ×800 (V)
	Dot Pitch	0.117 (H) ×0.117 (V) mm
	Aspect Ratio	16:9 / 4:3 Switchable
	Brightness (MAX)	400cd/m ²
	Contrast (MAX)	800:1
	Color Depth	8Bits(16.7M Colors space)
	Image processor	10Bits
	Response Time	12ms
	Viewing Angle	H 178° / V 178°

VIDEO IN	VF	20 pin VF Cable
-----------------	----	-----------------

Operation requirement	Input Voltage	DC 12V Standard 4 pin XLR
	Power Consumption(MAX)	11W
	Working Temperature	0-40℃
	Storage Temperature	-20-60℃
	Storage Humidity	0%-90% Non-coagulation

Structure	Shell Materials	ABS engineering material
	Dimensions (unit: mm)	207(w)X151(h)X60(d)
	Weight	About 1Kg
	Installation Device	Video Camera

Standard Accessories

	VF-701HDA
Fixing screws	2
VF Main line	1
U bracket	1
FoldableSunhood	1
Linear zoom trigger	1

* As per Manufacturer Catalogue Dated: 28/08/2017