

<b>VIDEO INPUTS</b>	3G/HD/SD-SDI, Composite	<b>VIDEO OUTPUTS</b>	1 x HDMI, 1 SDI
<b>TOTAL WINDOWS</b>	4	<b>HDMI (OG-MicroQ-RM)</b>	800x480 to 1920x1200 (1080p) 50/59.94/60Hz
<b>SERIAL DIGITAL</b>	SMPTE 424M, 292M, 259M	<b>RJ45 (OG-MicroQ-RMx)</b>	Up to 35 feet with passive receiver, Up to 115 feet with active receiver (option, HDMI-1-R)
<b>Equalization</b>	120m at 2.97 Gbps, 140m at 1.48 Gbps, 400m at 270 Mbps with Belden 1694A	<b>SDI</b>	Matching HDMI output resolution up to 3G
<b>Return Loss</b>	> 15db up to 1.485 Gbps< > 10db up to 3G	<b>ON-SCREEN DISPLAY</b>	Borders, Labels, Tallies, Audio meters, Alarm tags, Safe area markers
<b>Embedded Audio</b>	SMPTE-272M-A	<b>GPI</b>	8 for tally or AXP (ASCII command)
		<b>IP</b>	100 Base-T, TSL, AXP_Lite protocol
<b>COMPOSITE</b>	NTSC (SMPTE-170M), PAL (ITU624-2)	<b>POWER</b>	12V
<b>Signal Level</b>	1V nominal		
<b>DC Offset</b>	0V, + - 0.1V		
<b>Impedance</b>	75 ohm		
<b>Return Loss</b>	40db up to 5MHz		