

VIDEO INPUTS	4x 3G/HD/SD-SDI, Composite	VIDEO OUTPUTS	1 x HDMI, 1 SDI
TOTAL WINDOWS	4	HDMI	800x480 to 1920x1200 (1080p) 50/60 Hz
SERIAL DIGITAL	SMPTE 424M, 292M, 259M	SDI	Matching HDMI output resolution up to 3G
Equalization	120m at 2.97 Gbps, 140m at 1.48 Gbps, 400m at 270 Mbps with Belden 1694A	ON-SCREEN DISPLAY	Border, Label, Alarms and Audio Meters
Return Loss	> 15db up to 1.485 Gbps< > 10db up to 3G	GPI	8 for Preset recall or ASCII
Embedded Audio	SMPTE-272M-A	IP	100 Base-Tx, TSL, AXP
COMPOSITE	NTSC (SMPTE-170M), PAL (ITU624-2)	ELECTRICAL	12 W, 90-250V 50/60Hz
Signal Level	1V nominal	EMI / RFI	Complies with FCC Part 15, Class A, CE, EU, EMC, C-tick
DC Offset	0V, + - 0.1V	POWER	5 DC 3A
Impedance	75 ohm	SIZE	171 mm W x 120 mm D x 44.45 mm H
Return Loss	40db up to 5MHz	MOUNT	Magnetic