

VIDEO INPUTS	UHD (Quad 3G), 3G A&B/HD/SD-SDI Each UHD input will consume 4 SDI inputs	VIDEO OUTPUTS	4 SDI outputs (one per quadrant)
CONNECTOR TYPE	BNC IEC 61169-8 Annex A	AUDIO OUTPUTS	Embedded HDMI and SDI out
TOTAL WINDOWS	Maximum of 32 windows	OUTPUT RESOLUTION	3840x2160p 50/60Hz
SERIAL DIGITAL	SMPTE 424M, 292M, 259M	ON-SCREEN DISPLAY	Borders, labels, tally UMD, OMD, IMD, dynamic UMD
EQUALIZATION	120m at 2.97 Gbps, 140m at 1.48 Gbps, 400m at 270 Mbps with Belden 1694A	GENERAL PURPOSE I/O	Up to 64 inputs with RJ50 - DB9 connectors
RETURN LOSS	> 15db up to 1.485 Gbps > 10db up to 3G	SERIAL PORT	N/A
EMBEDDED AUDIO	SMPTE-272M-A	IP	100 Base-Tx, TSL, AXP Connector: RJ45
ALARMS	No audio, audio high/low, no video, video format display	ELECTRICAL	85W, 90-250V 50/60 Hz
EMI/RFI	Complies with FCC Part 15 Class A, CE, EU EMC, C-tick	POWER	Redundant 90-250 AC
SIZE	2 RU, 48.5 cm (19")		