

<b>Video Inputs</b>	MPEG2 transport stream, H.264, MPEG4	<b>Outputs</b>	2 DVI, HDMI (RJ45), SDI (optional)
<b>Connectors</b>	BNC IEC 61169-8 Annex A	<b>Output Resolution</b>	2048 x 1080 (1080P)
<b>Total Windows</b>	4, 8, 12, or 16	<b>On Screen Display</b>	Skin Technology for customizing borders, labes (4/window), fonts, tally LED, clock faces, logos, UMD, OMD, IMD
<b>Metadata</b>	AFD, WSS, Closed Captioning	<b>General Purpose IO</b>	Up to 24 inputs with DB9 connectors
<b>Audio, Video Decode</b>	MPEG2 / H.264 decode up to 4 video streams at 1080i Decode one stereo audio stream per video Stream	<b>Serial Port</b>	RS232 with RS422 or 485 option Connector: RJ45, Baud Rate up to 115200 Format, TSL, TSI, AXP
<b>Alarms</b>	No audio, audio high/low, no video, video black, video frozen	<b>IP</b>	100 Base-Tx, TSL, AXP, Connector: RJ45
<b>Control</b>	Front panel buttons for quick preset recalls, GPIs, Apantac ASCII Protocol (AXP), Director (config & control app)	<b>Electrical</b>	100W, 90-250V 50/60 Hz for 1RU 200W, 90-250V 50/60 Hz for 2RU
<b>Power</b>	Optional redundant power supply	<b>EMI/RFI</b>	Complies with FCC Part 15 Class A, CE, EU EMC, C-tick
<b>Size</b>	1RU 44.5 cm (17.5") W x 50 cm (19.7")D 2RU 44.5 cm (17.5") W x 60 cm (23.6")D		